

AIRBUS INDUSTRIE - CONSUMABLE MATERIAL LIST (CML) - SECTION : 12 - STRIPPERS									
Ref. item	Material/Product Supplier design./ description	Specification and/or Supplier s ref.	Supplier code	CML cat	Spl Lbl Y/N	Flash Point C(F)	Packaging, Shelf life, Transport, Remarks	Doc Code	Effective for a/c type
12-013	UTILIZATION RECOMMENDATIONS/RESTRICTIONS : SUITABLE ONLY FOR STRIPPING OF EXTERNAL PAINT SCHEME WITH INTERMEDIATE COAT.								
12-014	WATER BASED ACID ACTIVATED PAINT STRIPPER	REF TURCO 6776 L.0	D8908 F3172 H1540 61102	A	Y	+093 (+199)	PKG = 20,25,200 LITERS SL = 1 YEAR AT 5 TO 38 DEG C (41 TO 100 DEGF) COOL AND VENTILATED AREA TR = REF:IATA REGULATIONS		
OR									
12-014A	WATER BASED ACID ACTIVATED PAINT	REF CEE-BEE E-1004 JN	MC GEAN WOLVERHA IUK 02984				PKG = 20,25,200L SL = STORAGE TEMPERATURE: 5 DEG C TO 38 DEG C 41 DEG F TO 100 DEG F TR = REF:IATA REGULATIONS RMK = SHELF LIFE:1 YEAR RELATIVE HUMIDITY: COOL AND VENTILATED AREA		
OR									
12-014B	UTILIZATION RECOMMENDATIONS/RESTRICTIONS : REFER TO SRM 51-75-11 FOR LIMITATIONS (ON TIME PAINT STRIPPING)								
	51-75-11-201							SRM	310 600
	57-75-11-201							SRM	300